2025 **W230 ABS**









METALLIC OCEAN BLUE/EBONY

POWER		Front Tire Rear Tire	90/90-18 110/90-17
Engine	4-stroke, single-cylinder, SOHC, 2 valves, air- cooled	Front Brakes	Single 265mm disc with 2-piston calipers, ABS
Displacement	233cc	Rear Brakes	Single 220mm disc with 1-piston caliper, ABS
Bore x Stroke	Bore x Stroke 67.0 x 66.0mm DETAILS		
Ratio	5.0.1	Frame Type	Semi-double cradle, steel
Maximum Torque	14.0 lb-ft @ 5,800 rpm	Rake/Trail	27.0°/3.7 in
Fuel System	DFI® with 32mm throttle bodies	Overall Length	83.6 in
Ignition	TCBI with Digital Advance	Overall Width	31.4 in
Transmission	6-speed, return shift	Overall Height	42.9 in
Final Drive	Sealed chain	Ground Clearance	5.9 in
Electronic Rider Aids	Anti-lock Brake System	Seat Height	29.3 in
DEDEODMANOE		Dry Weight	293.2 lb**

PERFURMANCE

Front	3/mm teles
Suspension /	
Wheel Travel	
Rear Suspension	Twin shock
	1

scopic fork/4.6 in

/ Wheel Travel

s with spring preload adjustability/3.7 in

Ground Clearance	5.9 in
Seat Height	29.3 in
Dry Weight	293.2 lb**
Curb Weight	315.2 lb*
Fuel Capacity	3.1 gal
Wheelbase	55.7 in
Color Choices	Metallic Ocean Blue/Ebony

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.