Z650RS ABS





MSRP \$8.899







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

10.8:1

Compression

Ratio

Maximum

Torque

48.5 lb-ft @ 6,700 rpm

Fuel System

DFI® with Keihin 36mm throttle bodies

Ignition

TCBI with Electronic Advance

Transmission

6-speed, return shift

Final Drive

Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock

Brake System (ABS)

PERFORMANCE

Front
Suspension /
Wheel Travel

41mm telescopic fork/4.9 in

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable preload,

swingarm/5.1 in

Front Tire 120/70-17

Rear Tire 160/60-17

Front Brakes Dual 300mm petal-style discs with two-piston

calipers and ABS

Rear Brakes Single 220mm petal-style disc and ABS

DETAILS

Frame Type	Trellis, high tensile steel
Rake/Trail	24.0°/3.9 in

Overall Length 81.3 in

31.5 in **Overall Width**

Overall Height 43.9 in

Ground Clearance

4.9 in

31.5 in **Seat Height**

Dry Weight 383.7 lb**

Curb Weight 412.3 lb*

Fuel Capacity 3.2 gal

Wheelbase 55.3 in

Color Choices Ebony

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.