NEW 2025 **Z900 ABS**





MSRP **\$9,999 - \$10,299**

METALLIC SPARK BLACK/METALLIC CARBON GRAY/EBONY



GALAXY SILVER/METALLIC SPARK BLACK/PHANTOM BLUE



POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression Ratio 11.8:1

.

Maximum Horsepower 123.0 hp¹ @ 9,500 rpm

Maximum Torque

73.1 lb-ft @ 7,700 rpm

Fuel System

DFI® with 36mm throttle bodies

Ignition

TCBI with Electronic Advance

Transmission

6-speed, return shift

Final Drive

Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis

Orientation Awareness

PERFORMANCE

Front Suspension / Wheel Travel

41mm inverted telescopic fork with rebound damping and spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link, gas-charged rear shock with rebound damping and spring preload

adjustability/5.5 in

Front Tire 120/70-17

Rear Tire 180/55-17

Front Brakes Dual 300mm semi-floating discs with radial-mount 4-

piston calipers and ABS

Rear Brakes Single 250mm disc with single-piston caliper and ABS

DETAILS

Frame Type Trellis, high tensile steel

Rake/Trail 24.7°/4.3 in

Overall Length 81.3 in

Overall Width 32.7 in

Overall Height 43.3 in

Ground Clearance 5.7 in

Seat Height 31.9 in

Dry Weight 423.4 lb** / 425.6 lb** 50-State Model

Curb Weight 467.5 lb* / 469.7 lb* 50-State Model

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 5" All-digital TFT color instrumentation, All-LED

lighting, ERGO-FIT®, Smartphone Connectivity with Voice Command and Turn-by-Turn Navigation via

RIDEOLOGY THE APP MOTORCYCLE

Color Choices Metallic Spark Black/Metallic Carbon Gray/Ebony,

Galaxy Silver/Metallic Spark Black/Phantom Blue

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)

Specifications subject to change.

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.