## NINJA H2®R ABS





## \$59,100



MIRROR COATED MATTE SPARK BLACK



## **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

121.5 lb-ft @ 12,500 rpm

TCBI with Digital Advance

Sealed chain

6-speed, return shift, dog-ring

Displacement 998cc

**Bore x Stroke** 76.0 x 55.0mm

**Compression Ratio** 8.3:1

Maximum

321.5 hp1 @ 14,000 rpm Horsepower

**Maximum Torque** 

**Fuel System** 

Kawasaki Supercharger

Ignition

**Transmission** 

**Final Drive** 

**Electronic Rider Aids** 

**PERFORMANCE** 

Front Suspension / **Wheel Travel** 

43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

DFI® with 50mm throttle bodies (4) with dual injection;

Economical Riding Indicator, Kawasaki Cornering

Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine

Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-

Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper

Rear Suspension / **Wheel Travel** 

Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback reservoir, 30-way compression and rebound damping adjustability, 16-way spring preload adjustability, and topoutspring/5.3 in

120/60-17 V01F slick **Front Tire** 

**Rear Tire** 190/65-17 V01R slick

Dual 330mm semi-floating discs with dual radial-mount, **Front Brakes** 

opposed 4-piston Brembo M50 Monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

**Rear Brakes** Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

## **DETAILS**

**Frame Type** Trellis, high-tensile steel, with swingarm mounting plate

25.1° / 4.3 in Rake/Trail

**Overall Length** 81.5 in

**Overall Width** 33.5 in

**Overall Height** 45.7 in

**Ground Clearance** 5.1 in

**Seat Height** 32.7 in

**Dry Weight** 432.2 lb\*\*

**Curb Weight** 476.3 lb\*

**Fuel Capacity** 4.5 gal

Wheelbase 57.1 in

**Special Features** Supercharged engine, Carbon fiber aerodynamic downforce generating devices, Highly Durable Paint

**Color Choices** Mirror Coated Matte Spark Black

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.